

PRODUCT: PROOF W PRO

DESCRIPTION

ACRYLIC WATERPROOF MEMBRANE.

Resin in aqueous solution based on styrene-acrylic emulsion without organic solvent and free bituminous products. It forms film over 5°C. Good elasticity.

Specially designed for horizontal surfaces, high resistance to rubbing.

TECHNICAL DATES

Dry to the touch	4 hours
Density	1,53 g/cc.
Frost stability	Good
Re-paint	12-24 Hours
External resistance	Aliphatic. UV resistance.
Saponification resistance	Optimal
Adherence	Multi-adhesion
Finish	Semi-gloss
Recomended thickness	1500 µm
Performance, depends requirements	Between 0.5 y 2Kg/m²

APPLICATION

PROOF W PRO is developed for waterproofing in all phases of new construction and repairs old constructions. It forms elastic and easy to lengthen membrane, perfectly attached to the surface, which supports the structural movement preventing water from filtering. It supports the moderate traffic. The membrane has high durability. It has tack free.

STORAGE

Correct storage in it original container at temperatures between 5 y 40 °C. No storage more than twelve months.

SAFETY INFORMATION

PROOF W PRO is not toxic or flammable. Use without special safety measures is recommended; just legal conditions of occupational health are required.

DILUTION

READY TO USE. According to the porosity, can be solved like a primer.

CONTAINERS

Container: 22 Kg.